


General Notes:


- ALL WORK SHALL CONFORM TO THE LATEST FLORIDA BUILDING CODE, THE NFPA LIFE SAFETY CODE, AND ALL OTHER APPLICABLE CODES AND ORDINANCES. OBTAIN ALL REQUIRED PERMITS FOR THE PROPER LEGAL EXECUTION OF THE WORK DESCRIBED IN THESE DRAWINGS AND SPECIFICATIONS.
- PROVIDE A CONTINUOUS LOAD PATH FROM TRUSSES OR RAFTERS TO FOUNDATION FOR ALL NEW 2. CONSTRUCTION. IF ANY DISCREPANCIES, CALL DESIGNER FOR CLARIFICATION BEFORE PROCEEDING.
- THE CONTRACTOR SHALL VERIFY ALL EXISTING CONDITIONS PRIOR TO STARTING ANY WORK. HE/SHE 3. SHALL NOTIFY THE DESIGNER OF ANY DISCREPANCIES BETWEEN THE CONTRACT DOCUMENTS AND ACTUAL SITE CONDITIONS FOUND DURING OR PRIOR TO DEMOLITION.
- FOUNDATION DESIGN IS BASED ON 2000 PSF STABLE SOIL CONDITIONS. 4.
- PROVIDE TESTING ON SOIL COMPACTION PRIOR TO LAYING STEEL OR POURING CONCRETE. COMPACTION SHOULD ACHIEVE 95% MODIFIED PROCTOR DENSITY.
- PROVIDE ADEQUATE BLOCKING BEHIND ALL WALL MOUNTED FIXTURES 6.
- PROVIDE ALL ACCESSORIES, HARDWARE AND MISC. ITEMS AS PER DRAWINGS AND SPECIFICATIONS. ALL 7. ITEMS SHALL BE INSTALLED AS PER MANUFACTURERS WRITTEN INSTRUCTIONS AND CUT SHEETS.
- CONTRACTOR MUST VERIFY ALL DIMENSIONS PRIOR TO CONSTRUCTION. DO NOT SCALE DRAWINGS. 8.
- ALL CONCRETE SHALL BE 3000 PSI COMPRESSIVE STRENGTH AT 28 DAYS. 9.
- INSTALL DOORS AND WINDOWS PER MANF. DATA PROVIDED W/ PRODUCT. CENTER UNLESS NOTED 10.
- REFER TO WIND LOAD ANALYSIS FOR NAIL PATTERN AND SCHEDULE AND HOLD DOWN TABLES 11.
- 12. ATTIC OVER CONDITIONED SPACE IS UNVENTED. ATTIC INSULATION FOAM-IN-PLACE SPRAY FOAM INSULATION.
- 13. ATTIC OVER PORCHES IS VENTED. THE TOTAL NET FREE VENTILATING AREA SHALL NOT BE LESS THAN 1/150 OF THE AREA OF THE SPACE VENTILATED. VENTILATION OPENINGS HAVING A LEAST DIMENSION LARGER THAN 1/4 INCH (6.4 MM) SHALL BE PROVIDED WITH CORROSION-RESISTANT WIRE CLOTH SCREENING, HARDWARE CLOTH, OR SIMILAR MATERIAL WITH OPENINGS HAVING A LEAST DIMENSION OF 1/16 INCH (1.6 MM) MINIMUM AND 1/4 INCH (6.4 MM) MAXIMUM.
- 14. ALL FLASHING TO MEET CODES. FOLLOW MANUFACTURER'S DATA SHEET AND SMACNA STANDARDS.
- STRUCTURAL CONNECTORS LISTED ARE FOR EXAMPLE. OTHER PRODUCTS MAY BE SUBSTITUTED FOR 15. ANY CONNECTORS LISTED PROVIDED THEY MEET THE REQUIRED LOAD CAPACITIES. FOLLOW MANUFACTURER'S INSTALLATION DATA. ANY CONNECTORS EXPOSED TO THE WEATHER SHALL BE HOT DIPPED GALVANIZED.
- 16. ANCHOR BOLT MINIMUM EMBEDMENT IS 7" UNLESS OTHERWISE NOTED.
- 17. ELECTRICAL INFORMATION IS DIAGRAMMATIC ONLY.
- 18. ALL FIXTURES AND EQUIPMENT MUST MEET THE OWNER'S APPROVAL PRIOR TO PURCHASE AND INSTALLATION
- ALL WOOD IN CONTACT WITH MASONRY OR CONCRETE SHALL BE PRESSURE TREATED. ALL STRUCTURAL 19. WOOD EXPOSED TO WEATHER SHALL BE PRESSURE TREATED.
- 20. ALL WOOD AND WOOD CONSTRUCTION SHALL COMPLY WITH THE RELEVANT CODES AND SPECIFICATIONS AND THE 'AMERICAN INSTITUTE OF TIMBER CONSTRUCTION' (STANDARD MANUAL)
- 21. APPLICATION OF PAINT OR OTHER COATING SHALL BE IN STRICT ACCORDANCE WITH THE MANUFACTURER'S DIRECTIONS. READY-MIXED PAINT SHALL NOT BE THINNED, EXCEPT AS PERMITTED IN THE APPLICATION INSTRUCTIONS.
- 22. ALL SURFACES TO BE FINISHED SHALL BE CLEAN AND FREE OF FOREIGN MATERIALS, (DIRT, GREASE, ASPHALT, RUST, ETC.)
- APPLICATION SHALL BE IN A WORKMANLIKE MANNER PROVIDING A SMOOTH SURFACE. APPLICATION RATE 23. SHALL BE THAT RECOMMENDED BY THE MANUFACTURER. APPLICATION MAY BE BY BRUSH OR ROLLER, OR MAY BE BY SPRAY IF PAINT IS FORMULATED FOR SAME.
- 24. PROVIDE EXTERIOR AND INTERIOR SURFACE FINISHES AS SCHEDULED, AS APPROPRIATE FOR THEIR LOCATION OR EXPOSURE TO WEATHER, AND AS RECOMMENDED BY THE MANUFACTURER.
- 25. OTHER FINISHES AS PER CONSTRUCTION DOCUMENTS, FINISH SCHEDULE OR OWNER'S SPECIFICATIONS.
- THE DESIGNER SHALL NOT BE RESPONSIBLE FOR AND WILL NOT HAVE CONTROL OR CHARGE OF 26 CONSTRUCTION MEANS, METHODS, TECHNIQUES, SEQUENCES OR PROCEDURES. NOR WILL HE/SHE BI RESPONSIBLE FOR THE SAFETY PRECAUTIONS AND PROGRAMS IN CONNECTION WITH THE WORK, OR THE CONTRACTOR'S FAILURE TO CARRY OUT THE WORK IN ACCORDANCE WITH THE CONTRACT DOCUMENTS THE DESIGNER SHALL NOT BE RESPONSIBLE FOR OR HAVE CONTROL OR CHARGE OVER THE ACTS OR OMISSIONS OF THE CONTRACTOR, SUB-CONTRACTORS, OR ANY OF THEIR AGENTS OR EMPLOYEES, OR ANY OTHER PERSONS PERFORMING ANY OF THE WORK.











A0

OF


Sketch 2


Electrical Legend

-	
	Ceiling Fan
Ø	Recessed Can Light
\bigcirc	Pendant Light
\oplus	Ceiling Mounted Light
	Bathroom Vanity Light
	LED Strip Light - Provide all LED
\$	Light Switch
e \$	3 Way Light Switch
e \$	Exhaust Fan Switch
4⊕	120V Duplex - Number indicates h
gfci	120V Duplex - Ground Fault Inter
¢€	120V Duplex - Ground Fault Intern Enclosure
\bigtriangledown	CAT6 Data Connection
▼	Telephone Connection
TV	RJ6 Television Connection
9	Exhaust Fan
(2)	Smoke Detector

Electrical Genral Notes: 1.

All receptacle outlets not indicated as gfi (ground fault interrupted) shall be afci (arc fault circuit interrupted) All receptacle outlets indicated as WP are Ground Fault Interrupted Verify w/ Owner light fixtures to receive dimmers Home run all CAT6 data connections to router location. Provide data connection to outside for Cable, Satellite <u>and</u> DSL Internet. 4.







Mark Width Height

Exterior			
01	2' - 8"	6' - 8"	
02	2' - 8"	6' - 8"	
Interior			
03	2' - 6"	6' - 8"	
04	2' - 6"	6' - 8"	
05	2' - 8"	6' - 8"	
06	2' - 8"	6' - 8"	
07	4' - 0"	6' - 8"	
08	4' - 0"	6' - 8"	
09	2' - 8"	6' - 8"	
10	2' - 4"	6' - 8"	

	Window Schedule					
Mark	Width	Height	Description	Comments	Head He	ight Count
A	2' - 0"	5' - 0"	Single Hung		6' - 8"	1
В	3' - 0"	5' - 0"	Single Hung		6' - 8"	7
С	3' - 0"	3' - 2"	Single Hung		6' - 8"	2
D	3' - 0"	1' - 8"	Awning		6' - 8"	2
E	3' - 0"	1' - 8"	Casement Right		6' - 8"	2
F	3' - 0"	1' - 8"	Casement Left		6' - 8"	2



 \bigoplus



for refrigerator

tankless water heater


erupted In Water Resitant

D with Dimmable Drivers


s height above floor


erupted


Door Schedule			
Location	Description	Comments	
Living Room	3/4 Lite		
Porch	3/4 Lite		
Bath 1	Pocket Door		
Bath 2	Pocket Door		
Bedroom 1			
Bedroom 2			
Closet 1	Double Bi Fold Door		
Closet 2	Double Bi Fold Door		
Hall	Bi Fold Door		
Mech			




Floor Plan





























A4

OF