

| HEADER SCHEDULE       |                      |            |            |                                |            |         |
|-----------------------|----------------------|------------|------------|--------------------------------|------------|---------|
| MAXIMUM OPENING WIDTH | HEADER SIZE          | Jack Studs | King Studs | Simpson Strong -Tie Connectors |            |         |
|                       |                      |            |            | Top Plate                      | Header     | Holdown |
| 4' - 0"               | (3) 2x10             | (2) 2x6    | (3) 2x6    | H6                             | LSTA30     | DTT22*  |
| 6' - 0"               | (3)2X12              | (2) 2x6    | (3) 2x6    | H8                             | (2) LSTA30 | DTT22*  |
| 18' - 0"              | (3) 1-3/4" X 18" LVL | (3) 2x6    | (3) 2x6    | (2) H6                         | (2) LSTA30 | HTT4*   |

\* FIRST FLOOR - DRILL AND EPOXY HOT-DIPPED GALVANIZED THREADED ROD (1/2" DIAMETER FOR DTT22, 5/8" DIAMETER FOR HTT4), 6" EMBEDMENT.  
UPPER FLOORS - BOLT W/ THREADED ROD TO PLATE BELOW

NOTES:  
1. ALL LUMBER SHALL BE SOUTHERN PINE NO. 2 OR BETTER OR SPRUCE PINE FUR NO.2 GRADE OR STRONGER.  
2. USE PLYWOOD SPACERS BETWEEN HEADER PLIES AS REQUIRED TO MATCH STUD DEPTH.  
3. NAIL STUD PACKS TOGETHER WITH 16d GALV COMMON NAILS @8" O.C. STAGGERED.  
4. INTERIOR NON-LOAD BEARING WALL HEADERS SHALL BE NOT LESS THAN CODE MINIMUMS.  
5. USE 8d GALV. COMMON NAILS ON SIMPSON H6, FULLY NAILED.  
6. USE 10d GALV. COMMON NAILS ON SIMPSON CS16, FULLY NAILED.  
7. SIMPSON CS16 MAY BE SUBSTITUTED FOR LSTA30.  
8. INSTALL HEADER STRAPS FROM THE INSIDE FACE OF WALL. IF THE TABLE CALLS FOR 2 HEADER STRAPS AT 1 JACK STUD, INSTALL 1 STRAP ON INSIDE FACE OF WALL AND 1 STRAP ON THE EXTERIOR FACE OF WALL. STAGGER NAIL LOCATIONS AS REQUIRED.




AA002909 PH/FAX 352-3782518  
vraymos@gmail.com  
www.architectvraymos.com  
4825 SW 19th Street  
Gainesville FL 32608

SUBCONTRACTORS AND CONTRACTORS SHALL BE IN CONFORMANCE WITH APPLICABLE CITY, COUNTY, STATE AND FEDERAL CODES. ALL DISCREPANCIES WITH CONSTRUCTION DOCUMENTS SHALL BE BROUGHT TO THE ARCHITECT'S ATTENTION PRIOR TO PROCEEDING. VERIFY ALL FIELD CONDITIONS AND DIMENSIONS.;

THIS DRAWING IS PROTECTED BY COMMON LAW COPY RIGHTS AND MAY NOT BE REPRODUCED IN ANY WAY WITHOUT THE WRITTEN CONSENT OF THE ARCHITECT. CHANGES TO THE DRAWING MAY ONLY BE MADE BY THE ARCHITECT. ANY OTHER CHANGES SHALL BE CONSTRUED AS A DEROGATION OF THE ARCHITECT'S COPY RIGHTS OR OTHER RESERVED RIGHTS.

VICTOR E RAYMOS JR.  
ARCHITECTS SEAL  
NOT VALID WITHOUT ORIGINAL SIGNATURE, DATE & RAISED SEAL OR DIGITAL SEAL, DIGITAL SIGNATURE & DATE.



Gosslin Duplex  
South Building 15136-015-001

Job Number: 574  
Document Date: 07.17.2023

Rev Date Remark

Drafting by:  
BOB HARRIS  
bobharrisdesign.com  
bh@bobharrisdesign.com  
352-317-6644  
2351 SW 5th Avenue

Details  
A18  
OF  
21

Permit Set

Permit Set